

Specifications for Mini Strobe Lights

12VDC - 30VDC

2Watts / Double Flash


Description and Application

Light designed for vehicle safty on various vehicles

Applications include: Trucks, trailers mining equipment, forklifts, mining machines

Specifications

Electrical Specifications



Protection

Reverse Polarity

Operating conditions

Operating temperature (Ta): IP Rating Light

Colours available

Light Source

Construction

Materials	Poly
Length, Height, Width	118n
Weight	0.05
Hole Pitch	105n
Hole Size	3mm
Wire length supplied	30cn
Hazardous Gases	Cont
Warrantee	6 mc

Predicted Life Expectancy


@ 40deg ambient	
@ 30deg ambient	

	···· , ··· · · · ·
;	0.25 Amps
;	0.25 Amps
	Yes
	-40°C to +50°C
	IP68
	Red/Amber/White
	2835 High Power Leds
	Polycarbonate
	118mm, 23mm, 28mm
	0.05Kg
	105mm
	3mm, can be drilled to 5mm
	30cm white/red
	Contains Halides
	6 months Limited warrantee


-000

Part Code:	Colour
0106-00002	Red
0106-00001	Amber
0106-00003	White











35k hours 50k hours







100 Albertina Sisulu Road Roodepoort, Johannesburg South Africa 1724